



MEANWELL DRIVER

LRS Series

Operating altitude up to 5000 meters



Model No.	Output Power	Input Voltage	Waterproof Grade	Size/mm	Weight (KG)	Output Voltage	Output Current
LRS-35-12	35W	AC85~264V	IP30 & 3 Years	99*82*30	0.23kg	DC12V	3A
LRS-35-24						DC24V	1.5A
LRS-50-12	50W	AC85~264V	IP30 & 3 Years	99*82*30	0.23kg	DC12V	4.2A
LRS-50-24						DC24V	2.2A
LRS-75-12	75W	AC85~264V	IP30 & 3 Years	99*97*30	0.3kg	DC12V	6A
LRS-75-24						DC24V	3.2A
LRS-100-12	100W	AC85~264V	IP30 & 3 Years	129*97*30	0.34kg	DC12V	8.5A
LRS-100-24						DC24V	4.5A
LRS-150-12	150W	AC85~132V / 170~264V	IP30 & 3 Years	159*97*30	0.48kg	DC12V	12.5A
LRS-150-24						DC24V	6.5A
LRS-150F-12	150W	AC85 ~ 264V	IP30 & 3 Years	159*97*38	0.48kg	DC12V	12.5A
LRS-150F-24						DC24V	6.5A
LRS-200-12	200W	AC90~132V / AC180~264V	IP30 & 3 Years	215*115*30	0.66kg	DC12V	17A
LRS-200-24						DC24V	8.8A
LRS-350-12	350W	AC90~132V / AC180~264V	IP30 & 3 Years	215*115*30	0.76kg	DC12V	29A
LRS-350-24						DC24V	14.6A

LPV Series



Model No.	Output Power	Input Voltage	Waterproof Grade	Size/mm	Weight (KG)	Output Voltage	Output Current
LPV-20-12	20W	AC90-264V	IP67 & 2 Years	118*35*26	0.22kg	DC12V	1.67A
LPV-20-24						DC24V	0.84A
LPV-35-12	35W	AC90-264V	IP67 & 2 Years	148*40*30	0.34kg	DC12V	3A
LPV-35-24						DC24V	1.5A
LPV-60-12	60W	AC90-264V	IP67 & 2 Years	162*42*32	0.40kg	DC12V	5A
LPV-60-24						DC24V	2.5A
LPV-100-12	100W	AC90-264V	IP67 & 2 Years	190*52*37	0.63kg	DC12V	8.5A
LPV-100-24						DC24V	4.2A
LPV-150-12	150W	AC180-305V	IP67 & 2 Years	191*63*37	0.74kg	DC12V	10A
LPV-150-24						DC24V	6.3A

Modele sunt orientative. In functie de proiect, se pot utiliza si alte tipuri de surse in comutatie de la acelasi